

VENTILATING FAN



Power Cord



Plastic Guard



Impeller



Frame



A



B



C

FEATURES

- ◆ **Designed** For heat ventilation in the cabinet.
- ◆ **Manufactured** Designed with 2 Ball bearing Heavy duty. Impellers made from fiberglass reinforced plastic which comply to UL94V-0 and impedance protection.
- ◆ **Dimension** 120x120x38mm with Die-Cast Aluminum Housing and 7.0mm thickness, Black ABS plastic guard with 19" Germany Export Rack trademark.
- ◆ **Frame** Made from Electro-Galvanized Steel sheet in light gray color painted by Electrostatic powder coating process.
- ◆ **Power Cord**
1.80m, 2x0.5mm² (≈20AWG) for 1xØ4" Fan.
1.40m, 3x18AWG (≈0.82mm²) for 2xØ4", 3xØ4" Fan.
- ◆ **Manufacturer and Distributor** By ISO 9001:2015 Certification.

Technical Specification

- Speed : 2,650 rpm @ 50 Hz , 3,000 rpm @ 60 Hz
- Max. Air-Flow : 2.38 m³/min or 84.8 CFM
- Max. Input Power : 22 Watts @ 50 Hz , 19 Watts @ 60 Hz
- Acoustical Noise : 46 dB (A)
- Input Voltage : 220-230 VAC , 50/60 Hz
- Operating Temperature : -30°C to +70°C
- Life Expectancy : 50,000 Hours Continuous
- Approval : CE & UL/CSA

Options

- Color : *Black color (as requested)

ORDERING INFORMATION

Order No.	Description	Figure
G7-05001	1 x Ø 4" HEAVY DUTY FAN (Individual) w/Cable 1.8 M	A
G7-05002	2 x Ø 4" HEAVY DUTY FAN SET w/Cable 1.4 M	B
G7-05003	3 x Ø 4" HEAVY DUTY FAN SET w/Cable 1.4 M	C

* Order No. for Black Color : G7-050XXB

Sample : G7-05002B 2 x Ø 4" HEAVY DUTY FAN SET w/Cable 1.4 M., Black Color